



Series IG500, IG600 and IT600 Impact Door and Frame Quote/Order Request Form


Fax Completed Checklist to U.S. Aluminum Technical Sales at (866) 262-3299. Then call to discuss: (800) 262-5151 (U.S.), (877) 421-6144 (Canada), or (323) 588-1281 (International). Ask for Extension 15305. This form is also available online at usalum.com.

COMPANY NAME _____ PHONE _____
 CONTACT _____ ACCOUNT NO. _____ FAX _____
 JOB NAME _____ EMAIL _____

QUOTE ORDER P.O. # _____ DATE _____

SERIES	THICKNESS	STANDARD PROFILE DIMENSIONS		
		STILE	TOP RAIL	BOTTOM RAIL
IG500	2-3/16"	4-5/8"	4-11/16"	7-5/16"
IG600	2-3/16"	4-5/8"	4-11/16"	7-5/16"
IT600	2-3/16"	4-5/8"	4-11/16"	7-5/16"
Special Top Rail for Overhead Concealed Closer Bottom Rail Option			5-11/16"	10"

DOOR SWING CHART



Use the Door Swing Chart to determine how the door(s) should be handed.

OPENING TYPE	DOOR STILE	GLASS STOPS
<input type="checkbox"/> Door and Frame (Supply) <input type="checkbox"/> Frame Only (Supply) <input type="checkbox"/> Door Only (Supply) <input type="checkbox"/> Custom _____	IG500 IG600 IT600	<ul style="list-style-type: none"> • With 9/16" Glass Stops • With 1-5/16" Glass Stops • With 1-5/16" Glass Stops

DOOR FINISH

11 - Clear Anodized
 22 - Dark Bronze Anodized
 33 - Black Anodized
 52 - Bone White 70% KYNAR® (2-Coat)
 71 - Standard 70% KYNAR® (2-Coat)
 Standard Color per Chart - Specify _____
 71 - Custom 70% KYNAR® (2-Coat) - Specify _____
 71 - Custom 70% KYNAR® (3-Coat) - Specify _____

TOP RAIL

4-11/16" (Standard)
 5-11/16" for OHCC

BOTTOM RAIL

7-5/16" (Standard)
 10" Bottom

DOOR MUNTIN

7-5/16" Horizontal (only) (NON FPA)
 From Bottom of Door to Center Line of Muntin
 (Specify) _____

DOOR CLOSER

O.H. Concealed (Offset-Prep Only)
 Jackson 20-330
 LCN 2030
 90° 105°
 Hold Open Yes No
 Surface Mount
 Drop Plate
 Door Stop/Holder Degree _____
 No Closer Required

HARDWARE FINISH **DOOR FINISH**

• Clear 11, 12, 44, 52, 71
 • Bronze 22, 33
 Specify _____

DOOR HINGING

Continuous Geared Hinge (Florida Approval)
 1-1/2" PR Butt Hinges
 By USALUM By Others
NOTE: Prep Only Requires Manufacturer's Name,
 Model, and Template
 Manufacturer: _____
 Model: _____

LOCKING

A.R. MS Hookbolt With Cylinder/T-Turn - **STD**
 • Cylinder (Ext.) • Thumbturn (Int.)
 Flushbolts - DH008 - **STD**
 A.R. MS188 Two Points Flushbolts (Optional)

DOOR OPENING SIZE

36" x 84"
 Custom Single _____
 (FPA Maximum Size 36" x 96")
 72" x 84"
 Custom Pair _____
 (FPA Maximum Size 72" x 96")

CLEARANCES/THRESHOLDS

• These Thresholds Follow FPA Guidelines
 Clearance from Bottom of Door to Finish Floor
 TH811 3/8" (Air Threshold)
 TH800 1-3/4" (Air Water Threshold)
 (Includes IG570 Subsill)
 (Accessible Threshold Ramp Not Included)

DOOR SWING **QUANTITY**

LHR Hinge Left Swing Out _____ ea.
 RHR Hinge Right Swing Out _____ ea.
 PAIR Swing Out _____ ea.

FOR OFFICE USE ONLY

TAKEN BY: _____
 PRICED BY: _____
 EDITED BY: _____



Series IG500, IG600 and IT600 Impact Door and Frame Quote/Order Request Form

Fax Completed Checklist to U.S. Aluminum Technical Sales at (866) 262-3299. Then call to discuss: (800) 262-5151 (U.S.), (877) 421-6144 (Canada), or (323) 588-1281 (International). Ask for Extension 15305. This form is also available online at usalum.com.

PANIC DEVICES

- Concealed Vertical Rod Panics
- Jackson 1285
- Jackson 2086
- With Cylinder on Active Leaf
- Exit Only

FRAME SERIES

- Series IG500
- Series IG600
- Series IT600

UP/OVER FRAME

- Up/Over
- Up/Over
- Up/Over

TRANSOM FRAME

- Transom (120" Max Height)
- Transom (120" Max Height)
- Transom (120" Max Height)

PUSH/PULL HARDWARE

- Standard Push/Pull
- Offset Pulls
- None

ADDITIONAL NOTES OR SKETCHES

FOR OFFICE USE ONLY

TAKEN BY: _____

PRICED BY: _____

EDITED BY: _____

APPROV _____

DATE _____